



PRELIMINARY SPECIFICATIONS

ATA133 2.5" Series

E2A133BL

When Size and Performance Matter
 Enhanced Productivity and System Performance



Ideal for Storage Applications in:

- Enterprise Systems
- Desktop and Mobile Computing
- Database and OLTP Applications
- Business Intelligence/Decision Support
- Video-On-Demand
- Military and Aerospace
- Imaging Applications
- Industrial Automation
- Real-Time Data Acquisition
- Control and Instrumentation

E-Disk® Altima™ ATA133 2.5-inch Series

The future of storage is solid state, and BiTMICRO Networks, Inc. brings you the most advanced solid state disk (SSD) solution with the E-Disk® Altima™ series. Powered by BiTMICRO's proprietary "Enhanced Datamover and Storage Accelerator" (EDSA™) flash I/O controller and "Logical Unifier of Extensive Transfer Arrays" (LUNETATM) memory flash interface ASICs, E-Disk® Altima™ SSDs utilize high-density flash memory chips to create massive storage capacities in standard disk drive form factors. What's more, flash memory-based E-Disk® Altima™ SSDs boost system performance by eliminating seek time and latency for faster I/O and sustained transfer rates. With no moving parts, E-Disk® Altima™ SSDs set the bar for storage reliability, durability and endurance in all types of operating environments.

BiTMICRO Networks E-Disk® Altima™ ATA133 products offer optimum solution to address ever growing storage capacity requirements and performance demands of today's computing applications. It is designed without device driver requisites, making it easy to install and operate. Armed with patented FlashBus™ technology, E-Disk® Altima™ ATA133 offers random I/O rates of up to 20,000/sec, 133 MB/sec burst rate, sustained rates of up to 100 MB/sec, and storage capacities of up to 416 GB.

Increased High Speed Performance

- 133 MB/sec Burst Rate
- Up to 100 MB/sec Sustained Rate
- Up to 20,000 IOPS
- 30 to 100 µsec Access Time

Highest Storage Capacities

- 2.5-inch: 8 to 416 GB*

**Up to 64 GB at 9.5 mm height*

Industry Standard ATA Interface

- No Device Driver Required
- IDE to UDMA133 Support
- Completely Bootable

Unparalleled Operational Capabilities

- Pure Solid State/Non-Volatile
- 1,500 Gs Operating Shock
- -40 to +85°C
- 2 Million Hours MTBF
- 120,000 ft Altitude

Data Security Features

- DataSentinel
- PowerGuard®
- securErase®
- Write Protect

Compliance

- EMI: CE, FCC, AS/NZS
- Safety: TUV, UL
- EU RoHS 2002/95/EC
- China RoHS SJ/T 11363-2006

SPECIFICATIONS FOR  ATA133 2.5" SERIES
Flash Disk and Solid State Disk Storage Solutions

Performance Specifications:

Access Time	30 to 100 µsec
Burst Rate	133 MB/sec
Sustained Rate	Up to 100 MB/sec
I/O Operations per Second	Up to 20,000 IOPS
Fully Associative Cache	Up to 64 MB

Environmental Specifications:

Operating Temperature	Commercial	0 to 70 °C
	Industrial	-40 to +85 °C
Max Temperature Change Rate	3 C°/min	
Humidity	5 to 95% (Non-Condensing)	
Shock (Operating)	1,500 G	
Vibration (Operating)	16.4 G rms	
Altitude	-1,200 to 120,000 ft	
Airflow	None Required	

Power Requirements:

Input Voltage	5 VDC (±5%)	
Power Consumption	Write	TBD
	Read	TBD
	Idle	TBD

Reliability:

MTBF	>1.9 Million Hours at Bellcore Issue 6, Method I, Case 3
Bit Error Rate	<10 ⁻²⁷
Data Reliability	Built-in EDC/ECC Based on BCH Algorithm Corrects up to 9 Random Bit Errors per 528-Byte Block; Detects up to 10 Bit Errors
Data Integrity	10 years
Diagnostics	Built-In Power-Up Self Test Self-Monitoring Diagnostics Database

Endurance:

Write Endurance	8 GB	16 GB
	328 years @ 100 GB/day Erase/write Cycles	657 years @ 100 GB/day Erase/Write Cycles
Read Endurance	Unlimited	

Compatibility/Compliance:

ATA Compatibility	ANSI INCITS 397-2005 (ATA/ATAPI-7) Supports PIO Modes 0-4; UDMA Modes 0-6
EMI Compliance	CE, FCC, AS/NZS Regulations
Safety Compliance	TUV and UL
Security Erase Compliance	NISPOM DoD 5220.22-M, NSA 130-2, Air Force AFSSI 5020, Army 380-19, IRIG-106
RoHS Compliance	EU RoHS 2002/95/EC, China RoHS SJ/T 11363-2006

Physical Specifications:

Form Factor	2.5"	
Storage Capacity*	8 to 416 GB	
Dimension	Width	2.75 in (69.85 mm)
	Length	3.955 in (100.45 mm)
	Height	0.374 in (9.50 mm) to 0.999 in (25.38 mm)
Weight**	2.928 oz (83.00 gm) to 7.796 oz (221.00 gm)	
Mounting Considerations	HDD Industry Standard, All Orientations	
Connector	44-Pin 2.00 mm IDE/ATA ANSI Standards	

*1 GB = 1,024 MBytes; Up to 64 GB at 9.5 mm height
**Weights are approximate

Product Part Number:

Part Number Options	E2A133B + XXXXY + TGM + AC
XXXX: Capacity (GB) <i>Last digit denotes single decimal number</i> (e.g. 0080G = 8.0 GB, 4160G = 416.0 GB)	9.5 mm Height: 8, 16, 32, 64 >9.5 mm Height: 80, 160, 208, 288, 416
Y: Capacity Unit*	G: Gigabytes
T: Temperature	C: Commercial (0 to 70 °C) I: Industrial (-40 to +85 °C)
G: PowerGuard®	N: No PowerGuard® Option 1: Save Mode on Power Down 2: Erase Mode on Power Down 3: Standby Erase Mode on Power Down
M: Media Type	L: Large Block SLC NAND Flash
A: Casing	R: Rugged Casing
C: Coating	N: No Conformal Coating (Default) A: Acrylic Conformal Coating S: Silicone Conformal Coating
Example	E2A133B0080GCNLRN

*1 GB = 1,024 MBytes

BitMICRO's product specifications and engineering development objectives are subject to change at anytime without prior notice. All information provided herein is provided for design comparison and reference purposes only.

Copyright © 1999-2008. BitMICRO®, the BitMICRO Networks logo, FlashBus™, E-Disk®, Altima™, EDSA™, LUNETATM™, securErase®, PowerGuard®, and Ultimate Storage Solutions™ are trademarks or registered trademarks of BitMICRO Networks, Inc. Other names are trademarks or registered trademarks of their respective owners. U.S. Patent No. 5,822,251; 5,956,743; 6,000,006; 6,317,330; 6,496,939; 6,529,416; 6,744,635; 6,757,845; 6,970,890; 6,981,070. Other Patents Pending.

One gigabyte, or GB, equals 1,073,741,824 bytes when referring to solid state disk capacity. Unformatted capacity is approximately 10-15% less than advertised capacity due to space reserved for flash memory management purposes. Resulting usable storage capacity will vary based on various factors, such as type of operating system, file sizes, file formats, optional features, and application software.

BitMICRO® Networks, Inc. 47929 Fremont Boulevard, Fremont, CA 94538 USA +1-510-74E-DISK

DTS-MK-052-15 December 2008

